



ENHANCE THE OUTDOORS

Wall mounted LED luminaire with downward, up and downward light distributions, reliable for both indoor and outdoor applications. It is a luminaire designed to enhance any around the architecture solution, available in single-beam and double-beam versions, and a wide ange of optics, so it can meet different requirements of project.

Material: aluminum body with PMMA lens and tempered glass













QUICKINFO

Wall luminaire 1x6W, 3 high-power LEDs  
Input voltage DC24V  
C.V. power supply ordered separately  
Down light



DIMENSIONS



CODE	Optic	Light color	Control	Finish color	Luminous flux
2016W6	 spot 8° <b>0008</b>	 2700K <b>2780</b>	 ON/OFF	 black <b>03</b>	480lm
	 narrow 15° <b>0015</b>	 3000K <b>3080</b>			
	 medium 30° <b>0030</b>	 4000K <b>4080</b>			
	 elliptical 10°x40° <b>1040</b>				













QUICKINFO

Wall luminaire 2x6W, 6 high-power LEDs  
Input voltage DC24V  
C.V. power supply ordered separately  
Up and down light



DIMENSIONS



CODE	Optic	Light color	Control	Finish color	Luminous flux
2016W12	 spot 8° <b>0008</b>	 2700K <b>2780</b>	 ON/OFF	 black <b>03</b>	960lm
	 narrow 15° <b>0015</b>	 3000K <b>3080</b>			
	 medium 30° <b>0030</b>	 4000K <b>4080</b>			
	 elliptical 10°x40° <b>1040</b>				



