

PRODUCT DATASHEET

Last information update: Jun. 2025




ATLAS Ø160 600MM

LED bollard light for outdoor applications

BL01

Technical Features

Power	20W / 30W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	1,600 / 2,400 lm ±10%
Light distribution type	Symmetrical
Light colour / CCT	3000K
CRI	80
Source type	LED
LED number	60
MacAdam step	5
Power supply	Built-in
Control	ON/OFF
Protection index	IP65
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



Construction

High weather-resistant powder painted aluminum body, PC optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Surface mounted with base.

Finish Colours

4 standard colours. Other RAL colours on request.

Wiring

Power input cable OPEN END 200 mm



Optional Accessories



anchor bolts
material: galvanised steel

B01

Ordering Information

example: BL01.20600WA+B01

BL01 · +

product	power	height	finish colour	accessory
BL01	20 20W	600 600MM	WA RAL9006	B01 ANCHOR BOLTS
	30 30W		JB RAL9005	
			AG RAL7016	
			TG RAL7043	