

PRODUCT DATASHEET

Last information update: Mar. 2025




CUBE-4

0822W20

Architectural LED floodlight for outdoor applications

Technical Features

Power	20W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	1,000 lm ±10%
Light distribution type	Symmetrical
Beam angle	Ultra spot 2°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	4
MacAdam step	5
Power supply	Built-in
Control	ON/OFF
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C



Construction

High weather-resistant fluorocarbon painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Surface mounted with adjustable base (standard).

Finish Colours


RAL9023 Pearl Dark Grey (standard). Other RAL colours on request.

Wiring

Power input cable OPEN END 1,000 mm




Optional Accessories




anti-glare grille (for models with optics <= 30°)
*can not be ordered separately

A01




honeycomb louvre
*can not be ordered separately

A02




anti-glare visor
*can not be ordered separately




A06




U-bracket
*can not be ordered separately



A11




adapter (for Φ48mm poles)
*can not be ordered separately



A12




clamp (for Φ114mm poles)
*can not be ordered separately



A13




plate (for Φ67~325mm T>=4 poles)
*can not be ordered separately



A14




strap (for Φ168~268mm trees)
*can not be ordered separately



A15



spike
*can not be ordered separately



A16

Ordering Information

example: 0822W20.0002.2780.01+A01

0822W20 · · · +

product	beam angle		light colour / CCT		finish colour		accessory	
CUBE-4-20W ultra spot	0002	2°	2780	2700K RA80	01	RAL9023	A01	anti-glare grille
			3080	3000K RA80			A02	honeycomb louvre
			4080	4000K RA80			A06	anti-glare visor
							A11	U-bracket
							A12	pole adapter
							A13	pole clamp
							A14	pole plate
							A15	strap
							A16	spike