


PRODUCT DATASHEET

Last information update: Jun. 2025



Wiring

Power input cable OPEN END 200 mm



EIKO 1000MM

BL02

LED bollard light for outdoor applications

Technical Features

Power	15W / 30W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	1,200 / 2,400 lm ±10%
Light distribution type	Symmetrical
Light colour / CCT	3000K
CRI	80
Source type	LED
LED number	60
MacAdam step	5
Power supply	Built-in
Control	ON/OFF
Protection index	IP65
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C

Construction

High weather-resistant powder painted aluminum body, PC optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C


Installation

Surface mounted with base.

Finish Colours

4 standard colours. Other RAL colours on request.

Optional Accessories



anchor bolts
material: galvanised steel

B02

Ordering Information

example: BL02.151000WA+B02

BL02 · +

product	power		height		finish colour		accessory	
BL02	15	15W	1000	1000MM	WA	RAL9006	B02	ANCHOR BOLTS
	30	30W			JB	RAL9005		
					AG	RAL7016		
					TG	RAL7043		