



PRODUCT DATASHEET

Last information update: Mar. 2025



Wiring

Power input cable OPEN END 1,000 mm
DMX input cable MALE connector 1,000 mm
DMX output cable FEMALE connector 1,000 mm



GOCCIA-6

1916W30

On-ground LED floodlight for outdoor applications

Technical Features

Power	30W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	1,350 lm ±10%
Light distribution type	Symmetrical / elliptical
Beam angle	9°, 15°, 20°, 30°, 45° / 15°x60°
Light colour / CCT	RGBW
CRI	-
Source type	LED (4-IN-1)
LED number	6
MacAdam step	-
Power supply	Built-in
Control	DMX512 (built-in DMX decoder)
Protection index	IP66
Impact resistance	IK08
Lifetime	50,000 hours Ta=25°C

Construction

High weather-resistant fluorocarbon painted die-cast aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C






Installation

Surface mounted with adjustable base (standard).

Finish Colours

RAL9023 Pearl Dark Grey (standard). Other RAL colours on request.

Optional Accessories

	anti-glare grille (for models with optics <= 30°) *can not be ordered separately	A01
	honeycomb louvre *can not be ordered separately	A02
	anti-glare glass *can not be ordered separately	A04
	leader cable with female 4-pin waterproof connector for DMX * specify cable length to complete order	LC4
	extension cable with male and female 4-pin waterproof connector for DMX * specify cable length to complete order	EC4

Ordering Information

example: 1916W30.0009.4130K.01+A01

1916W30 · · · +

product	beam angle		light colour / CCT		finish colour		accessory	
GOCCIA-6-30W	0009	9°	4130K	RGB+3000K	01	RAL9023	A01	anti-glare grille
	0015	15°	4140K	RGB+4000K			A02	honeycomb louvre
	0020	20°					A04	anti-glare glass
	0030	30°					LC4	leader cable
	0045	45°					EC4	extension cable
	1560	15°x60°						