

PRODUCT DATASHEET

Last information update: Mar. 2025



UNI-LINE

2608W15

Linear LED contouring light for outdoor applications

Technical Features

Power	15W
Input voltage	DC24V (constant voltage)
Insulation class	III
Delivered flux	1,100 lm ±10%
Light distribution type	Direct-view
Beam angle	120°
Light colour / CCT	2700K, 3000K, 4000K
CRI	80
Source type	LED
LED number	60
MacAdam step	5
Power supply	Not included
Control	ON/OFF
Protection index	IP65
Impact resistance	IK05
Lifetime	50,000 hours Ta=25°C

Construction

Anodized extruded aluminum body, polycarbonate diffuser.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C

Installation

Surface mounted with non-adjustable bracket (standard).

Finish Colours

Aluminum body, milky diffuser (standard).

Wiring

Power input cable MALE connector 200 mm
Power output cable FEMALE connector 200 mm



Ordering Information

example: 2608W15.0120.2780.01

2608W15 · · ·

product	beam angle		light colour / CCT		finish colour	
UNI-LINE-15W	0120	120°	2780	2700K RA80	01	aluminum
			3080	3000K RA80		
			4080	4000K RA80		