




PRODUCT DATASHEET

Last information update: Mar. 2025



Wiring

Power input cable OPEN END 200 mm
DMX input cable MALE connector 1,000 mm
DMX output cable FEMALE connector 1,000 mm



YORK-S

2507W32(0.3)

Linear LED wallwasher for outdoor applications

Technical Features

Power	32W
Input voltage	AC100-240V
Insulation class	I
Delivered flux	1,440 lm ±10%
Light distribution type	Symmetrical / elliptical
Beam angle	15°, 20°, 30°, 45°, 60° / 25°x45°
Light colour / CCT	RGBW
CRI	-
Source type	LED (4-IN-1)
LED number	24
MacAdam step	-
Power supply	Integrated
Control	DMX512 (built-in DMX decoder)
Protection index	IP66
Impact resistance	IK07
Lifetime	50,000 hours Ta=25°C

Construction

Powder painted extruded aluminum body, tempered glass cover, polycarbonate optical lenses.

Temperature Limits

Ambient operating temperature	from -20°C to +50°C
Storage temperature	from -40°C to +70°C



Installation

Surface mounted with adjustable bracket (standard).

Finish Colours

RAL9003 Signal White (standard). Other RAL colours on request.

Optional Accessories

	leader cable with female 4-pin waterproof connector for DMX * specify cable length to complete order	LC4
	extension cable with male and female 4-pin waterproof connector for DMX * specify cable length to complete order	EC4

Ordering Information

example: 2507W32(0.3).0015.4130K.01+LC4(specify length)

2507W32(0.3) · · · +

product	beam angle		light colour / CCT		finish colour		accessory	
YORK-S-32W (300MM)	0015	15°	4130K	RGB+3000K	01	RAL9003	LC4	leader cable
	0020	20°	4140K	RGB+4000K			EC4	extension cable
	0030	30°						
	0045	45°						
	0060	60°						
	2545	25°x45°						